

STANDARD EQUIPMENT

UPEMME

Two double effect hydraulic cylinders
Blocking valve so to hold in safe and secure manner
HARDOX[®] slides under the bucket

1

UEMME

INDEX

UEMME

4 Upper grip profiles with "jaws"

DESCRIPTION

4

UEMME

2

Multifunction bucket 4 in 1 suitable to be installed on large Wheel Loaders, Backhoe Loaders and Telehandlers. Each model is standard equipped by 2 double effect **hydraulic cylinders** and **blocking valve**. The internal profiles of the upper grip have a **particular shape** that allows to catch and keep even the most irregular material in place. The attention to details and any first rate equipment used in the structure, makes all B4-XL buckets valid tools of excellent quality.

B4-XL

3

4 IN 1 BUCKET



MODELS		B4-XL 2100	B4-XL 2300	B4-XL 2450
Width	mm	2120	2320	2470
Depth	mm	1080	1080	1080
Height	mm	1265	1265	1265
SAE capacity	m³	1,46	1,60	1,7
Weight without linkage	Kg	630	660	690
the day and the	Tons	4,5÷6	6÷8	8÷10

OPTIONS olted teeth and security remo

LINKAGE SYSTEMS

5 Bolted teeth and security removable protection

Universal linkage for Skid-Steer Loader Non universal linkage for Skid-Steer Loader Wheel Loaders, Backhoe Loaders and Telehandlers linkage









APPLICATIONS

- INDUSTRIAL SECTOR
- BUILDING SECTOR
- EXCAVATION AND BACKFILLING OPERATIONS
- WASTE, DEBRIS CLEARANCE

