

STANDARD EQUIPMENT

- 1 Grip actioned by two hydraulic cylinders
- 2 Blocking valve so to hold in safe and secure manner
- 3 HARDOX® slides under the bucket

DESCRIPTION

Grapple bucket with grip ideal for safely loading large quantities of material thanks to the presence of a **blocking** valve. In each model it is possible to bolt a side panels \boldsymbol{kit} so to increase the bucket capacity and a \boldsymbol{double} \boldsymbol{cut} **underblade** avoiding bucket cutting edge's wear. The entire range has been specifically designed for use on





MODELS		BM-XL 2100	BM-XL 2300	BM-XL 2450
Width	mm	2120	2320	2470
Depth	mm	1080	1080	1080
Height	mm	1265	1265	1265
SAE capacity	m³	1,65	1,80	1,92
Weight without linkage	Kg	695	730	760
the day after the	Tons	4,5÷6	6÷8	8÷10

OPTIONS

- 4 Bolted and reversible underplate
- Couple of bolted sides ables to increase the bucket capacity

LINKAGE SYSTEMS

Universal linkage for Skid-Steer Loader Non universal linkage for Skid-Steer Loader

Wheel Loaders, Backhoe Loaders and

Telehandlers linkage

APPLICATIONS

- BUILDING AND INDUSTRIAL SITES
- RECYCLING PLANTS
- RUBBLE REMOVAL
- DEMOLITION SECTOR
- WASTE HANDLING IN LANDFILL SITES
- COMPOSTING PLANTS

